

Refrigerant Male Connection (AM)

The AM range offers four caps designed for male refrigerant inlets/outlets. Ergonomic handles ensure easy installation and removal, even with gloves. Available in multiple sizes, each cap provides robust protection against leaks, dust, liquids, and contaminants for durable, reliable performance.

Applications:

The AM range offers caps for male refrigerant inlets/outlets, ensuring a secure fit and protecting critical connections essential to NEV thermal management systems.

Main features:



Ideal solution for male refrigerant inlets/outlets



Suitable for Automotive segment






Sealing features for tight closure



Made of Recycled LDPE



Easy plug in & removal



Properties

Standard colour: Natural

Standard material: Recycled LDPE

DBI Ref.	ϕA mm	E mm	ϕK mm	QTY Bag/Box
AM0067A-AA	6,4	17	14,1	4480/4480
AM0097A-AA	9,6	17	17,3	3696/3696
AM0130A-AA	13	19	20,5	3136/3136
AM0161A-AA	16,1	19	23,7	3000/3000

Counterpart dimensions:

DBI Ref.	ϕa mm	ϕb mm	c mm	ϕd mm	e mm	Description
AM0067A-AA	$\phi 6,35$	$\phi 6,7$	11,95	$\phi 10,95$	17	STLA Module 6
AM0097A-AA	$\phi 9,45$	$\phi 6,7$	11,95	$\phi 14,25$	17	STLA Module 8
AM0130A-AA	$\phi 12,7$	$\phi 6,7$	11,95	$\phi 17,35$	19	STLA Module 10
AM0161A-AA	$\phi 15,8$	$\phi 6,7$	11,95	$\phi 20,55$	19	STLA Module 12